

**INSTALLATION INSTRUCTIONS FOR
DYNOMAX KIT: 39487**

2010-07 Chevrolet/GMC Silverado / Sierra 2500HD/3500
6.6L Duramax Diesel (DPF)



2701 N. Dettman Rd.
Jackson, MI 49201

DANGER WARNING: SHOULD THE PURCHASER DECIDE TO INSTALL ANY EXHAUST PRODUCT AT HOME, BE WARNED THAT PASSENGER CAR OR LIGHT DUTY TRUCK/VAN "BUMPER" JACKS ARE INTENDED FOR EMERGENCY USE ONLY. THE USE OF FRAME CONTACT JACK STANDS IN CONJUNCTION WITH A FLOOR JACK AS MAIN SUPPORT IS HIGHLY RECOMMENDED TO MINIMIZE ACCIDENTAL DROPPING OF A VEHICLE DURING THE INSTALLATION PROCESS.

NOTE: Read all instructions before beginning the installation.

1. Remove the OE muffler muffler/tail pipe welded assembly. Use WD-40, or a similar product, to lubricate and help remove the metal rod hangers from the rubber isolators.
2. Install DynoMax front adapter pipe **51066 & 36491 gasket** to the outlet of the OE diesel particulate filter (DPF). Finger tighten the inlet flange fasteners..
3. Slip a 5" stainless steel band clamp over the inlet end and install DynoMax muffler **24233**. Slightly tighten the inlet clamp.
4. Slip a 5" stainless steel band clamp over the outlet end of the 24233 muffler and install front tail pipe **53714**. Insert the rod hanger into the rubber isolator on the chassis hanger. Slightly tighten the tail pipe inlet clamp. Please refer to the system diagram.

5. Slip a 5" stainless steel band clamp over the inlet end of rear tail pipe **53715** and install on the outlet of 53714. Insert rod hanger into the rubber isolator on the chassis hanger. Slightly tighten the rear tail pipe inlet clamp.
6. Slip a 5" stainless steel band clamp over the inlet end and install 304SS tip **36483**.
7. Beginning at the inlet of the system, position all components and tighten the clamps. Please see the full system diagram on the back page.

KIT CONTAINS:

- (1) 24233 MUFFLER
- (1) 51066 PIPE
- (1) 53714 PIPE
- (1) 53715 PIPE
- (1) 36483 SS TIP
- (1) 36491 GASKET
- (1) 36490 BOLT KIT
- (4) 5" BAND CLAMPS
- (1) 709875 INSTRUCTION SHEET

39487 SYSTEM DIAGRAM

