INSTALLATION INSTRUCTIONS FOR DYNOMAX KIT: 39509

2014-11 Ford F250, F350 Super Duty 6.7L Powerstroke Diesel (DPF)



2701 N. Dettman Rd. Jackson, MI 49201

DANGER WARNING: SHOULD THE PURCHASER DECIDE TO INSTALL ANY EXHAUST PRODUCT AT HOME, BE WARNED THAT PASSENGER CAR OR LIGHT DUTY TRUCK/VAN "BUMPER" JACKS OR SCISSOR JACKS ARE INTENDED FOR EMERGENCY USE ONLY. THE USE OF FRAME CONTACT JACK STANDS IN CONJUNCTION WITH A FLOOR JACK AS MAIN SUPPORT IS HIGHLY RECOMMENDED TO MINIMIZE ACCIDENTAL DROPPING OF A VEHICLE DURING THE INSTALLATION PROCESS.

DPF: Diesel Particulate Filter

NOTE: Read all instructions before starting any work.

- Remove the OE extension pipe (if equipped) and the tail pipe/resonator assembly that are installed behind the DPF. Do not remove the DPF. Use WD-40, or similar product, to lubricate and help remove the metal rod hangers from the rubber isolators.
- 2. Depending on the wheelbase / cab type of your truck, install the correct extension pipe per the list below. Use gasket 31723 as required and bolt kit **36490**. Reference the system diagram on back page.

W.B./Cab Type Extension Pipe Required

137" / Reg. No extension pipe required. Bolt 53785 directly to

outlet of DPF

141.8" / Super 51077 156.2" / Crew 52491

158" / Crew 51078 & 53786 after cutting 14" off inlet end of

53786. Use 5" clamp.

172.4" / Crew **51078** & **53786**. Use 5" clamp.

- Install over-axle tail pipe 53785 using gasket 31723 and bolt kit 36490.
 Slip the rod hangers into the rubber isolators. Please reference the system diagram.
- 4. Slip a 5" band clamp over the inlet end of **53787** tail pipe and install. Insert the rod hanger into the rubber isolator.
- 5. Slip a 5" band clamp over the inlet end and install 304SS tip 36483.
- 6. Beginning at the inlet end of the system, position all components and tighten the clamps and bolts. Please see the full system diagram on the back page

KIT CONTAINS:

(1) 51077 PIPE

(1) 52491 PIPE

(1) 51078 PIPE

(1) 53786 PIPE

(1) 53785 PIPE

(1) 53787 PIPE

(1) 36483 SS TIP w/5" BAND CLAMP

(2) 31723 GASKETS

(2) 36490 BOLT PACK

(2) 5" BAND CLAMP

(1) 711620 INSTRUCTION SHEET

Form: 711620 Revised 01/14

39509 SYSTEM DIAGRAM 36490 36490 36483 5" Clamp 53787 31723 31723 51077 (141.8" W.B.) 53785 52491 (156.2" W.B.) 51078 53786 (158" 172.4" W.B.)

Form: 711620 Revised 01/14